



# AVC-SFP-FX Datasheet

恩创致力于将先进的信息技术带入工业控制与工业信息领域。



安通恩创信息技术（北京）有限公司

[www.avcomm.cn](http://www.avcomm.cn)

电子邮箱: [sales@n-tron.com.cn](mailto:sales@n-tron.com.cn)

电话: (010) - 82859971

地址: 北京市海淀区马甸东路19号金澳国际公寓3105

## Product Features

- Duplex LC receptacle optical interface compliant
- Single 3.3V power supply
- Hot-pluggable
- 1310nm FP laser transmitter
- 10km link with 9/125µm Single -mode fiber
- AC-coupled Differential LVPECL inputs and outputs
- LVTTTL Receiver loss of signal output
- Optional DDM/ DMI function
- External calibration for DDM/DMI
- Class 1 laser safety certified
- Operating case temperature: -40 to +85°C
- RoHS compliant



## Applications

- FAST Ethernet
- Local Area Network(LAN)/  
Metropolitan Area Network(MAN)
- Ethernet/PDH/SDH

## Descriptions

AVC-SFP-FX-10 SFP transceivers, according to Small Form Factor Pluggable Multi-Sourcing Agreement (MSA) SFF-8074i and SFF-8472, revision 9.5, are designed for data communication on single mode fiber up to 10km. They are compliant with IEEE Std 802.3-2005 Gigabit Ethernet 100Base-LX and Fiber Channel FC- PI-2 Rev.8.0.

AVC-SFP-FX-10 SFP transceivers offer a wide range of design options, including Digital Diagnostic Monitoring (DDM) features.

AVC-SFP-FX-10 are compliant with RoHS.



## Ordering Information

Model Name	Description
AVC-SFP-FX-10	100M SFP optical port module, single mode 10km, wide temperature
AVC-SFP-FX-10-D	100M SFP optical port module, single mode 10km, wide temperature, DDM

## Installation dimensions

Unit: mm

