



AVC-SFP-FX-S Datasheet

恩创致力于将先进的信息技术带入工业控制与工业信息领域。



安通恩创信息技术（北京）有限公司

www.avcomm.cn

电子邮箱: sales@n-tron.com.cn

电话: (010) - 82859971

地址: 北京市海淀区马甸东路19号金澳国际公寓3105

Product Features

- Compliant with ITU-T G.957,G.958
- Multi-Source Package with Duplex LC Connector
- Up to 155Mb/s Data Rate
- 1310nm FP Multi-Mode
- Single +3.3V Power Supply
- Hot-Pluggable
- Eye Safety Designed to Meet Laser Class1, Compliant with IEC60825-1
- RoHS Compliant Products Available
- Operating case temperature: -40 to +85°C



Applications

- SONET OC-3/SDH STM-1
- SDH STM-1, I-1
- Fast Ethernet
- Other Optical Links

Descriptions

AVC-SFP-FX-S SFP transceivers, according to Small Form Factor Pluggable Multi-Sourcing Agreement (MSA) SFF-8074i and SFF-8472, revision 9.5, are designed for data communication on multimode fiber up to 2km. They are compliant with IEEE Std 802.3-2005 Ethernet 100BASE-SX and Fiber Channel FC- PI-2 Rev.8.0AVC-SFP-FX-S SFP transceivers offer a wide range of design options, including Digital Diagnostic Monitoring (DDM) features. AVC-SFP-FX-S are compliant with RoHS.

Ordering Information

Model Name	Description
AVC-SFP-FX-S	100M SFP optical port module, 1310NM,multi-mode 2km, wide temperature



Installation dimensions

Unit: mm

